

2.0 Monitor

By ReproScan

The ReproScan 2.0 Monitor offers bright and clear ultrasound images. With a convenient sunshade case, wireless capabilities, a built-in 8 hour battery and IP63 weatherproofing it is more versatile than ever.

Features & Specifications

- 2.4 GHz Wireless Receiver
- IP63 rated water and dust resistance
- Sunlight Readable with LED backlight
- VGA, HDMI, NTSC / PAL Multi-System Input
- 8 channel 2.4G WIFI video input
- 4:3 or 16:9 Aspect Ratio
- High resolution display
- High Performance Image and Video Processor
- Anti-Reflective / Fingerprint Coating

Display Specifications

- Screen Size: Diagonal 8" (4:3)
- Physical Resolution: 800 (H) x 600 (V)
- Dot Resolution: 2400 x 600 = 1,440,000 (dots)
- Supported Resolution: 640 x 480 ~ 1920 x 1080
- Contrast Ratio: 500:1

Electrical Specifications

- Power Supply: DC 12V
- Power Consumption:
 - Suspended Mode < 2W (Max.)
 - Continuous Mode < 10W (Max.)
 - Charging Mode < 24W (Max.)

Physical Specifications

- Video Source Input (RGB, RCA, HDMI, 2.4G WIFI CVBS video)
- Dimension (In) : 8.97 (L) x 6.69 (H) x 2.08 (D) In
- Weight (lb) : 3.08 lbs (w/o battery)

Other Specifications

- Operating Temperature: -4°F ~ 158°F (Not included battery)
- Storage Temperature: -22°F ~ 176°F (Not included battery)
- FCC, CE, Certification, ROHS, and IP63 Compliant
- 12 Month Warranty









2.0 Monitor

By ReproScan

Accessories

Ram Mount Kit





Compatible Devices

Flexx by ReproScan



BoviScan HD






ReproScan XTC

BoviScan Linear







S-60



1374 State Highway 92, Winterset, IA 50273 1.877.890.2411 • <u>www.repro-scan.com</u> SIMPLE • DURABLE • AFFORDABLE